

## DATASHEET

SPECIFICATIONS OF LUMINARY.	
Luminaries wattage	45 Watt (+/- 5%)
Input Voltage	230 VAC
Input Frequency	50 Hz
Input Current	0.205A
Power Factor	> 0.96
Athd.	CLASS C
Efficiency	>86%
Temperature Class	T6
IP Standard	IP 65
Total Weight	2.5 Kg
Starting Time	Instant ( 0.2 Sec)
Light Spreading Angle	120° x 60°
Guarantee	3 Years on LED DRIVER
Guarantee	5 Years on COB LED
Guarantee	3 Years on FLUX/CCT/CRI


ORDERING CODE: MFL45MW



SPECIFICATIONS OF LED		MAKE : CITIZEN JAPAN
Model No	CLU-038-1205 V6	
LED type / No of LED Lamp	COB/ Single	
Total Lumen (As per simulation Tool)	5329	
Lumen Efficacy (Lm/ Watt)	135 lm/W @ 60°C LED Tc	
Lumen Efficacy (Lm/ Watt) (Incl. all losses)	118 lm/W @ 60°C LED Tc	
Color / Color Rendering index	CCT 6500K / RA 70	
SP Ratio	2.25	2.25
MAC ADAM ELIP STAGE	STEP 3	
LED -Wattage/Current/Voltage	39.4 W / 1050 mA /37.6 V	
Lamp Life	1,60,000 Hours Min.	
Certifications / Reports	LM80/Photo Bio. Test	
Actual Tested Report	Actual Operating test Report for 63,000Hrs	
Identification Method	Unique Serial No. Printed on each Lamp	

**CITIZEN**  
Micro HumanTech

### LED SPECTRUM



SPECIFICATIONS OF LED DRIVER		MAKE - MEANWELL
Model No	PLD-60-1050	
Type of Driver	Constant Current	
Input Voltage Range	185 - 295 VAC	
Frequency Range	47 - 63 Hz	
Inrush current	Cold Start 25A	
Leakage current	0.5mA/ 277VAC	
Output Protection	Short Circuit, Over Voltage/ Current/ Temperature	
Withstand Voltage	I/P-O/P : 3.75KVAC	
Surge Protection	L-N : 2KV, L,N-PE : 4KV	
MTBF /DMTBF	458.852 Khrs min	
Capacitor Life Cycle	42086 Hrs @ 50°C	

SPECIFICATIONS OF OPTICS	
Optics Type	Glass Lens
MOC of Optics	Borosilicate Glass
Optics Efficiency	96%

SPECIFICATIONS OF FIXTURE \ HEAT SINK	
Certification	IP 65
MOC Fixture	Aluminum Diecasting
Junction Temperature -Tj	87°C
Case Temperature- Tc	60°C