

## DATASHEET

ORDERING CODE: MECOHB100MW


SPECIFICATIONS OF LUMINARY.	
Luminaries wattage	100 Watt (+/- 5%)
Input Voltage	230 VAC
Input Frequency	50 Hz
Input Current	0.469A
Power Factor	> 0.96
Athd.	CLASS C
Efficiency	91.5%
Temperature Class	T6
IP Standard	IP 40
Total Weight	3Kg Approx.
Starting Time	Instant ( 0.2 Sec)
Light Spreading Angle	60°/90°/120°
Guarantee	3 Years on LED DRIVER
Guarantee	5 Years on COB LED



SPECIFICATIONS OF LED		MAKE : CITIZEN JAPAN
Model No	CLU-048-1212 V6	
LED type / No of LED Lamp	COB/ Single	
Total Lumen (As per simulation Tool)	12019	
Lumen Efficacy (Lm/ Watt)	132 lm/W @ 77° C LED Tc	
Lumen Efficacy (Lm/ Watt) (Incl.all loses)	120 lm/W @ 77° C LED Tc	
Color / Color Rendering index	CCT 6500K / RA 70	
SP Ratio	2.25	2.25
MAC ADAM ELIP STAGE	STEP 3	
LED -Wattage/Current/Voltage	91.1 W / 2450 ma /37.2 V	
Lamp Life	1,00,000 Hours Min.	
Certifications / Reports	LM80/Photo Bio. Test	
Actual Tested Report	Actual Operating test Report for 63,000Hrs	
Identification Method	Unique Serial No. Printed on each Lamp	

**CITIZEN**  
Micro HumanTech

### LED SPECTRUM



SPECIFICATIONS OF LED DRIVER		MAKE - MEANWELL
Model No	ELG-100-42	
Type of Driver	Constant Current	
Input Voltage Range	100 - 305 VAC, 142 - 431 VDC	
Frequency Range	47 - 63 Hz	
Inrush current	Cold Start 60A	
Leakage current	0.75mA/ 277VAC	
Output Protection	Short Circuit, Over Voltage/ Current/ Temperature	
Withstand Voltage	I/P-O/P : 3.75KVAC	
Surge Protection	Line-Earth 6KV, Line-Line 4KV	
MTBF /DMTBF	282.9 Khrs min.	
Capacitor Life Cycle	52859 Hrs @ 60°C	

SPECIFICATIONS OF OPTICS	
Optics Type	Glass Lens
MOC of Optics	Borosilicate Glass
Optics Efficiency	96%

SPECIFICATIONS OF FIXTURE \ HEAT SINK	
Make of Fixture	Eminent Lighting Company
Certification	IP 40
MOC Fixture	Aluminum Extrusion - 6063
Junction Temperature -Tj	106°C
Case Temperature- Tc	77°C