

DATASHEET

SPECIFICATIONS OF LUMINARY.	
Luminaries wattage	60 Watt (+/- 5%)
Input Voltage	230 VAC
Input Frequency	50 Hz
Input Current	0.274A
Power Factor	> 0.95
Athd.	CLASS C
Efficiency	88%
Temperature Class	T6
IP Standard	IP 65
Total Weight	12.5 Kg Approx.
Starting Time	Instant (0.2 Sec)
Guarantee	3 Years on LED DRIVER
Guarantee	5 Years on COB LED
Guarantee	3 Years on FLUX/CCT/CRI


ORDERING CODE: MFLPCR60MW



SPECIFICATIONS OF LED		MAKE : CITIZEN JAPAN
Model No	CLU-028-1204 2Nos V6	
LED type / No of LED Lamp	COB/ Single	
Total Lumen (As per simulation Tool)	7008 lm	
Lumen Efficacy (Lm/ Watt)	136 lm/W @ 60°C LED Tc	
Lumen Efficacy (Lm/ Watt) (Incl. all losses)	116 lm/W @ 60°C LED Tc	
Color / Color Rendering index	CCT 6500K / RA 70	
SP Ratio	2.25	2.25
MAC ADAM ELIP STAGE	STEP 3	
LED -Wattage/Current/Voltage	53.4 W / 1400 mA /38.4 V	
Lamp Life	1,60,000 Hours Min.	
Certifications / Reports	LM80/Photo Bio. Test	
Actual Tested Report	Actual Operating test Report for 63,000Hrs	
Identification Method	Unique Serial No. Printed on each Lamp	

CITIZEN
Micro HumanTech

LED SPECTRUM



SPECIFICATIONS OF LED DRIVER		MAKE - MEANWELL
Model No	PLD-60-1400	
Type of Driver	Constant Current	
Input Voltage Range	180 - 295 VAC	
Frequency Range	47 - 63 Hz	
Inrush current	Cold Start 25A	
Leakage current	0.5mA/ 240VAC	
Output Protection	Short Circuit, Over Voltage/ Current/ Temperature	
Withstand Voltage	I/P-O/P : 3.75KVAC	
Surge Protection	L-N : 2KV, L,N-PE : 4KV	
MTBF /DMTBF	458.85 Khrs min.	
Capacitor Life Cycle	42086 Hrs @ 50°C	

SPECIFICATIONS OF OPTICS	
Optics Type	Glass Lens
MOC of Optics	Borosilicate Glass Lens
Optics Efficiency	90%(+/-5%)

SPECIFICATIONS OF FIXTURE \ HEAT SINK	
Make of Fixture	Sudhir Switch Gear
Certification	IP 65
MOC Fixture	Aluminum Diecasting-LM6
Junction Temperature -Tj	82°C
Case Temperature- Tc	60°C